

Datasheet



SMBus:	Level 3	Weight:	9-lbs 8-oz
Charge Rate:	3.0 Amps	Material:	ABS GSM
10 Bays:	Sequential	Color:	Black
Charge Time:	3 hours each	Dimensions:	24.5x4.6x7.7 in
Recalibration:	SMBus 12V@1.2A		622x117x196 mm
Recal Time:	less than 9 hours		Wall mounts on 16" centers

Target Batteries: SBS-3002-202 36, 36s, 201, 202, NI2020, ME202A, ME202B, ME202BB, ME210, PS202, TR36, TR202, 35, 35s, 17, 15, 15s, 30, 30s, GP36, GP202, GP35, GP201, LIP2020 any chemistry with SMBus or dumb NiCd / NiMH batteries with the standard battery AMP connector and 10K ohm NTC.

Agency Approvals:				
--------------------------	---	---	--	---

All Powerbases include: Chargers
 300W - Universal Switching Power Supply
 Options: Line cords (specify country)

Sales Office:
 Energy Access, Inc.
 7445 Hollingsworth Drive
 Indianapolis, IN 46268
Phone: 317-848-3585
Fax: 317-848-3845

Other Models:	Description
SBS-3010-201	10 Bay 3.0Amp Gang Charger
SBS-3010-202	10 Bay 3.0Amp Gang Charger
SBS-3010-204	10 Bay 3.0Amp Gang Charger
ICS-1010-35	10 Bay 1.0Amp Gang Charger
ICS-1010-36	10 Bay 1.0Amp Gang Charger