

Datasheet



SMBus:	Level 3
Charge Rate:	3.0 Amps
2 Bays:	Sequential
Charge Time:	3 hours each
Recalibration:	SMBus 12v@1.2A
Recal Time:	less than 9 hours
Weight:	9.5oz
Material:	ABS GSM
Color:	Black
Dimensions:	4.89x6.89x2.02 in 124x175x50 mm

Target Batteries: 201, 35, 35s, 17, 15, 15s, any chemistry with SMBus or dumb NiCd / NiMH batteries with 10K ohm NTC.

Agency Approvals:



TUV



Class B
FC
Cisper 22

The SBS-3002 includes: Charger
PS-2524 - Universal Switching Power Supply
Options: Line cords (specify country)
VA-2524 - Vehicle Power Adapter

<u>Other Models:</u>	<u>Description</u>
SBS-3002-201	2 Bay 3.0Amp
SBS-3002-202	2 Bay 3.0Amp
SBS-3002-204	2 Bay 3.0Amp
SBS-3010-201	10 Bay 3.0Amp Gang Charger
SBS-3010-202	10 Bay 3.0Amp Gang Charger
SBS-3010-204	10 Bay 3.0Amp Gang Charger

Sales Office:
Energy Access, Inc.
7445 Hollingsworth Drive
Indianapolis, IN 46268
Phone: 317-848-3585
Fax: 317-848-3845