

Datasheet



SMBus: Level 3
Charge Rate: 3.0 Amps
2 Bays: Sequential
Charge Time: 3 hours each
Recalibration: SMBus 12v@1.2A
Recal Time: less than 9 hours
Weight: 9.5oz
Material: ABS GSM
Color: Black
Dimensions: 4.89x6.89x2.02 in
 124x175x50 mm

Target Batteries: SBS-3002-202 36, 36s, 201, 202, NI2020, ME202A, ME202B, ME202BB, ME210, PS202, TR36, TR202, 35, 35s, 17, 15, 15s, 30, 30s, GP36, GP202, GP35, GP201, LIP2020 any chemistry with SMBus or dumb NiCd / NiMH batteries with the standard battery AMP connector and 10K ohm NTC.

Agency Approvals:				
--------------------------	---	---	---	--

All SBS-3002 includes: Charger
 PS-2524 - Universal Switching Power Supply
Options: Line cords (specify country)
 VA-2524 - Vehicle Power Adapter

Sales Office:
 Energy Access, Inc.
 7445 Hollingsworth Drive
 Indianapolis, IN 46268
Phone: 317-848-3585
Fax: 317-848-3845

<u>Other Models:</u>	<u>Description</u>
SBS-3002-201	2 Bay 3.0Amp
SBS-3002-202	2 Bay 3.0Amp
SBS-3002-204	2 Bay 3.0Amp
SBS-3010-201	10 Bay 3.0Amp Gang Charger
SBS-3010-202	10 Bay 3.0Amp Gang Charger
SBS-3010-204	10 Bay 3.0Amp Gang Charger