

# APC-C021 Series DC-DC CONVERTER

## 25W Single Output , Encapsulated



## Outline Product Specification

### FEATURES

- ❑ Low profile: 50.8 mm x 50.8 mm x 9.91 mm (2in. X 2in. X 0.39in.) with standoffs, (9.53mm (0.375in.) with standoffs recessed)
- ❑ Efficiency: 87% typical
- ❑ Fixed frequency
- ❑ Wide input voltage range: 36Vdc to 75Vdc
- ❑ Adjustable output voltage: 90% to 110% of  $V_o$ , nom
- ❑ Metal case
- ❑ Case ground pin
- ❑ Operating case temperature range:  $-40^{\circ}\text{C}$  to  $110^{\circ}\text{C}$
- ❑ Remote on/off
- ❑ Output overvoltage clamp
- ❑ Overcurrent protection
- ❑ Input undervoltage lockout
- ❑ Synchronisation
- ❑ Designed to meet UL60950, EN60950 and CE mark requirement

The APC-C021 series power modules are low-profile, cost effective board mountable DC/DC converters, which operate over an input voltage range of 36Vdc to 75Vdc and provide precisely regulated single DC output.

The output is fully isolated from the input, allowing versatile polarity configurations and grounding connections.

The output is fully isolated from the input, allowing versatile polarity configurations and grounding connections.

The converters have a maximum power rating of 25watts at a typical full-load efficiency of 87%.

The power modules are suited for board level applications in a distributed power architecture requiring isolated

### Options

- Choice of remote on/off logic configuration
- Short pin:  $2.79\text{mm} \pm 0.25\text{mm}$  ( $0.11\text{ in} \pm 0.01\text{ in}$ )

**2 Year Warranty**



## APC-C021 Single Output DC-DC Converter

48V(36V to 75V) Input, 3.3V & 5V Output, 25W max.

### Range

Model Number	Input Voltage (V)	Output Voltage (V)	Output Current (A)	Efficiency (%)
APC-C021-048-050-F	48	5.0	5	89
APC-C021-048-033-F	48	3.3	6	83
APC-C011-048-050	48	5.0	4	87
APC-C011-048-033	48	3.3	4.8	83

### Mechanical Outline

