

Datasheet



Charge Rate:	max 3.0 Amps
Charge Range:	2V - 24V
Weight:	6.0 oz
Material:	ABS GSM
Color:	Black
Connector:	2.1mm
Polarity:	Center Positive
Dimensions:	3.63x2.27x2.04 in 92 x 58 x 52 mm

Target Batteries: Lithium-Ion (Li+), Lithium-Ion Polymer (LiPB), Nickle Metal Hydride (NiMH), Sealed lead Acid (SLA), Nickle Cadmium (NiCd)

Agency Approvals:



TUV



Class B
FC
Cisper 22

All ICS includes:

Charger in standard housing
6" 3-conductor lead stripped and tinned

Options:

WA-1018 - 18W UL Wall Adapter
PS-1024 - 24W Universal Switching Power Supply
PS-2524 - 60W Universal Switching Power Supply
LC-00 - Line cords (specify country)
VA-1012 - Vehicle Power Adapter
VA-1018 - Vehicle Power Adapter
VA-2524 - Vehicle Power Adapter

Sales Office:

Energy Access, Inc.
7445 Hollingsworth Drive
Indianapolis, IN 46268
Phone: 317-848-3585
Fax: 317-848-3845



ICS-xxxx-xxxxx Target Batteries: Lithium-ion, Lithium-polymer, Nickel Metal Hydride, Nickel Cadmium and Sealed Lead Acid. Charge rates from 500mA to 3.0Amps. Single cell to 12 cells in series.



ICS-1002 Target Batteries: 35, 35s, 36, 36s, 30, 30s, 17, 15, 15s, dumb NiCd / NiMH batteries with the standard battery AMP connector and 10K ohm NTC.



ICS-1502 Target Batteries: SLA and NiMH



Power Base
ICS-3010-xxxxx
Charges 10 batteries in 5 hours.