

## POWER ENTRY MODULE, FILTERED, K SERIES

### FEATURES AND SPECIFICATIONS



#### OPTIONS

PART NUMBER	RATED CURRENT	IEC CONN	FUSE	ON/OFF SWITCH	VOLT SELECT
K1-12S10E	3A	YES	YES	YES	NO
K3-12VS10E	3A	YES	YES	NO	YES
K3-12S10EVS	3A	YES	YES	YES	YES
K3-123	3A	YES	YES	NO	NO

#### SPECIFICATIONS

##### 1.0 HIGHPOT RATING:

LINE-TO-GROUND: 2000 VAC  
 LINE-TO-LINE: 1750 VDC

##### 2.0 RATED VOLTAGES AND FREQUENCY:

115/250 VAC, 47-63 Hz

##### 3.0 MAXIMUM LEAKAGE CURRENT, EACH LINE TO GROUND.

115 VAC, 60 Hz: 0.25 mA MAX  
 250 VAC, 60 Hz: 0.50 mA MAX

##### 4.0 PERFORMANCE

MHz.		0.05	0.15	0.50	1.50	5.00	20.00	30.00
CM	L/G	30 dB	60 dB	65 dB	65 dB	65 dB	65 dB	65 dB
DM	L/L	10 dB	50 dB	65 dB	65 dB	65 dB	65 dB	65 dB

#### APPLICATIONS

- \* MICROPROCESSORS
- \* DATA TERMINALS
- \* SMPS WITH ON-BOARD FILTER

#### FEATURES

- \* MINIMUM SPACE REQUIREMENT
- \* COST SAVING INTREGRATION
- \* SAFETY INTERLOCK ON FUSE



## POWER ENTRY MODULE, FILTERED, K SERIES

