



Energy Access Incorporated

Smart Battery Series



SMBus	Level 3
Charge rate	3000 mA
2 Bays	Sequential
Recalibration	SMBus 12v@1.2A
Connector	2.5mm
Weight	15.5oz (440g)
Material	ABS GSM
Color	Black
Dimensions	6.89" x 4.89" x 2.30" (175mm x 124mm x 58mm)

Target Batteries: Any SMBus compliant battery with a standard 5-blade connector
 These include type SBS-3002 36, 36s, 201, 202, 201, SM201, SM202, SM204, NI2020, ME202A, ME202B, ME202BB, ME210, PS202, TR36, TR202, 35, 35s, 17, 15, 15s, 30, 30s, GP36, GP202, GP35, GP201, LIP202
 Unit may be adapted for other configurations as well.

The SBS-3002 includes

Charger
 PS2524 - Universal Switching Power Supply

Optional components

Line cord (specify country)
 VA2524 - vehicle power adapter

Other Models:	Description
SBS-3002-201	2 Bay Sequential
SBS-3002-202	2 Bay Sequential
SBS-3002-204	2 Bay Sequential
SBS-3010-201	10 Bay Gang Charger
SBS-3010-202	10 Bay Gang Charger
SBS-3010-204	10 Bay Gang Charger

Agency Approvals:		Class B FC Cispr 22	
--------------------------	--	----------------------------------	--

Datasheet

Models

SBS-3002-201



SBS-3002-202



SBS-3002-204



Custom

